Static Solutions, Inc. 43 Broad Street Hudson, MA 01749 HEALTH 1 FLAMMABILITY 0 REACTIVITY 0

#### **MATERIAL SAFETY DATA SHEET**

Page 1 of 4 AF-5500 ANTI-STATIC FLOOR FINISH

SECTION I PRODUCT IDENTIFICATION

Product Trade Name: Anti-static floor finish

Chemical Name: Acrylate Copolymer, water based dispersion

Supplier: Static Solutions, Inc.

Effective Date: 1/1/2014

Formula: (-CH2-CH(COOR)-)n

Molecular Weight: n> 100

SECTION II HAZARDOUS INGREDIENTS

Ingredient Weight % TLV PEL(TWA) STEL CAS Number
Ammonium Hydroxide 1 max. 25 ppm 50 ppm 35 ppm 1336-21-6 Acute

(Immediate) Inhalation Hazard

Ingredient

May contain one or more of the following:

Glycol Ether DM 10 max. not est. not est. not est. 111-77-3

SECTION III COMPOSITION INFORMATION

Approx. Wt% SARA 313 CAS Number

Water 65 min. 7732-18-5
Acrylate Copolymer 25 max. Proprietary
Glycol Ether coalescent 10 max. yes See Sect. IV

Tri(butoxyethyl) Phosphate 2 max. 78-51-3

Zinc Oxide Complex 1 max. yes 1314-13-2

SECTION IV PHYSICAL DATA

Boiling Point: 212 degrees F Freezing Point: Variable

Specific Gravity (Water=1): Variable

Percent Volatile by Weight: 65% Water minimum

Vapor Density (Water Vapor=1): 1

Evaporation Rate (Water=1): 1

Solubility in Water: Infinitely miscible

pH: 7.0 to 9.5

Appearance and Odor: Clear or translucent with mild odor

SECTION V TOXICOLOGICAL PROPERTIES

LD50: Not determined
Threshold Limit Value: No limit determined

Effects of Acute Exposure:

Ingestion: Nausea may occur.

# Static Solutions, Inc. 43 Broad Street Hudson, MA 01749

**MATERIAL SAFETY DATA SHEET** 

Page 2 of 4

AF-5500 ANTI-STATIC FLOOR FINISH

#### SECTION V CONT'D TOXICOLOGICAL PROPERTIES

Inhalation: Prolonged exposure may produce headaches.

> And mucous membrane irritation. Direct contact may cause irritation.

**Eve Contact:** Direct contact may cause irritation. Effects of Chronic Exposure: None determined.

#### **SECTION VI PREVENTIVE MEASURES**

#### INDUSTRIAL HYGIENE IN THE WORKPLACE

Respiratory Protection: None required in well ventilated areas. An approved organic

vapor full face respirator is advised for poorly ventilated areas.

Ventilation: Local Exhaust: None required.

Skin Contact:

Mechanical (General): Provide adequate ventilation.

Protective Gloves: Wear rubber gloves.

Eve Protection: Wear approved safety glasses with side shields.

Other Protective Equipment: Wear protective work clothing.

STORAGE AND HANDLING PROCEDURES

Precautions To Be Taken In Handling And Storage: Store at 40 degrees F to 90 degrees F. This product is for Industrial Use only. Keep away from Fire and Heat (Any ignition source). Keep containers closed when not in use. Provide adequate ventilation.

Steps To Be Taken In Case Material is Released Or Spilled: Halt spill at source and contain or dike spill with inert absorbent material. Transfer liquid to containers for recovery or disposal. Shovel absorbent into drums for disposal in accordance with local, state, and federal regulations.

Recommended Waste Disposal Methods: Material should not be flushed into sewer system. If this product becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, since it has neither the characteristics of Subpart C nor is listed in Subpart D. After the material has been collected, dispose of in accordance with all regulations applicable to non-hazardous liquid wastes.

#### **SECTION VII FIRST AID MEASURES**

### EMERGENCY FIRST AID PROCEDURES

Induce vomiting if conscious, and call a physician. Ingestion:

Inhalation: Remove to fresh air and consult physician if symptoms persist. Promptly wash with soap and water, and rinse thoroughly. Skin Contact:

Remove contaminated clothing and shoes.

**Eye Contact:** Promptly flush with a large amount of water for at least 15

minutes. Contact a physician if symptoms persist.

#### SECTION VIII REGULATORY INFORMATION

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 - (SARA TITLE III)

Section 302 - Extremely Hazardous Substances (40 CFR 355): This product does not contain materials listed in Appendix A or B as an Extremely Hazardous Substance.

# Static Solutions, Inc. 43 Broad Street Hudson, MA 01749

**MATERIAL SAFETY DATA SHEET** 

Page 3 of 4

AF-5500 ANTI-STATIC FLOOR FINISH

#### SECTION VIII CONT'D REGULATORY INFORMATION

Sections 311/312 - Material Safety Data Sheet Requirements (40 CFR 370): Materials listed in 29CFR 1910, Subpart Z are identified in Section IV. None are known or suspected carcinogens listed by the National Toxicology Program, International Agency for Research on Cancer, or OSHA. Section 313 - List of Toxic Chemicals (40 CFR 372): Listed materials contained in this product are identified in Sections III or IV of this MSDS.

#### TOXIC SUBSTANCES CONTROL ACT (TSCA)

The chemical ingredients in this product are on the 8(B) Inventory List (40 CFR 710). CLEAN AIR ACT AMENDMENTS OF 1990

This product does not contain, and has not contacts during manufacture, any Ozone Depleting Substances.

SECTION IX	FIRE AND EXPLOSION HAZARD DATA
Flash Point:	Greater than 250 degrees F.
Auto ignition Temperature:	Greater than 250degrees F.
Extinguishing Media:	CO2, Dry Chemical.
Flammable Limits: Lower:	Not Applicable.
Upper:	Not Applicable.
Special Fire fighting Procedures:	Toxic gases may be released. Use self-contained
breathing apparatus.	
Unusual Fire/Explosion Hazards:	None.
SECTION X	HAZARD RATING INFORMATION
Hazard Ratings:	

Hazaru Katings.				
4 = Extreme	HMIS	Hazard	NFPA	
3 = High	1	Health	1	
2 = Moderate	0	Flammability	0	
1 = Slight	0	Reactivity	0	
0 = Insignificant		•		

SECTION	XI REACTIVITY DATA
Stability:	Stable
Conditions to Avoid:	Temperatures of 212 degrees F. or over will
	boil water away.
Incompatibility:	Treat as water.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Thermal decomposition on burning may
	produce toxic gasses.
SECTION XII	USER'S RESPONSIBILITY

**Static Solutions, Inc.** cannot anticipate all conditions of handling and use of this product. Therefore, **Static Solutions, Inc.** accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products.

# ERIALS SAFETY DATA SHEET PAGE 4 of 4 AF- 5500 ANTI-STATIC FLOOR FINISH SECTION XII CONT'D USER'S RESPONSIBILITY

It is the responsibility of the user to provide a safe workplace, using the health and safety information obtained herein as a guide. **Static Solutions, Inc.** will accept no liability for damage or loss incurred from the improper handling and use of this product.

Revised 7/28/04 Revised 1/1/14 Revised 10/14/04 Revised 2/4/11